




DESCRIPTION

Elenora series is a combination of slim design modern style for illuminating urban roads and parking lots.

We used the latest solid state technology from Philips for a long life illuminance and high efficiency. All our outdoor fixtures are rated for wet locations and offers variety of mounting options.

18-1/2"(H) x 12-5/8"(W) x 3-1/2"(D)









Ordering Example: LI-FDL300

ORDERING INFORMATION							
Model	Watts	Lumen	Optic	ColorTemp.	CRI	Optional	Finish
LI-FDL300	300	40500	$A = 120 \times 90$	1=4000K 2=5000K	>83	1 = Dimmable 2 = PhotocellYes	
	300	40500	$B = 150 \times 105$		>83		BR







LIGHTING SPECIFCATION Dimmable: 0~10V Dimming

- Lens: TYPE III TIR optic Lens
- LED: Philips Lumileds Luxeon 3030 High flux LED
- Solid state lighting technology for long life, no maintenance needed and high-efficiency
- Cord type: 6' SJTW 18/3 AWG cable • Total lumens: 39000LM/37300LM
- Color temperature: 5000K/4000K/3000k
- Color rendering index: 82~84
- Beam Angle: 120°x90

HOUSING SPECIFICATIONS:

- Die-cast Aluminum housing with powder coat finish (Dark Bronze)
- Operating temperature: -40°F to 104°F
- Lifespan: 70,000 hr.
- IP Rating: IP65
- Effective projected areas (EPA's) are:

Front = 0.38 square feet Side = 0.50 square feet Face = 1.75 square feet





















Phone: 800-784-0698







PHOTOMETRIC:











Phone: 800-784-0698





MOUNTING OPTIONS:








M1


M2


M3

LENS TYPES ILLUSTRATED




Type 2 is still linear but wider in the front to accommodate 4 lane roadways, or wider drive lanes.





Type 4 (commonly known as a "Forward Throw" or Asymmetric) Is best along perimeters where spill light is a concern or there are no place to add poles within a site.



Type 5 - is available in a round or square pattern. Best suited for interior areas within a site or on the median of 4-6 lane roadways.



Phone: 800-784-0698